


# RIDGED TOP V 벨트



## H15 Topgrip (Reinforced)



이름	BXH(mm)	TRACTION RATING(DN)	ELONGATION (%)	RECOMMENDED PULLEY(mm)	MINIMUM PULLEY(mm)
H15GAR13TO	13 X 15	A	30	160	145
H15GAR13TO	17 X 20	B	50	180	160
H15GAR13TO	22 X 25	C	75	275	250

## DEL/FLEX Topgrip



DFVR13TO	13 x 15	A	20	5	150	135
DFVR17TO	17 x 20	B	36	5	160	145
DFVR22TO	22 x 25	C	60	5	260	230

## SOUPLEX Topgrip (Reinforced)




SXVWAR13TO	13 X 15	A	25	0.5	135	120
SXVWAR17TO	17 X 20	B	40	1	145	130
SXVWAR22TO	22 x 25	C	60	1.5	250	230

## SOUPLEX Topgrip



SXVM13TO	13 X 15	A	12	8	130	110
SXVM17TO	17 X 20	B	22	8	140	120
SXVM22TO	22 X 25	C	36	8	240	220


## DEL/AFLEX Shape I - 7각



DFVR13F1	13 X 15	*A	28	5	160	140
DFVR17F1	17 X 20	B	50	5	220	180
DFVR22F1	22 X 25	C	81	5	270	220

\* 주문에 의한 제작


## DEL/FLEX Shape II - 5각



DFVR13F2	13 X 15	A	28	5	160	140
DFVR17F2	17 X 20	B	50	5	240	200
DFVR22F2	22 X 25	C	81	5	300	260

	경도	Recommended Tensioning	Steel	Stainless Steel	H.D.P.E
DEL/FLEX	90A	3-6%	0.5	0.6	0.25
SOUPLEX	85A	5-8%	0.6	0.7	0.35
H15 (심체형)	90A		0.45	0.55	0.25
SOUPLEX (심체형)	85A		0.6	0.7	0.35

# Cogged RIDGED TOP V 벨트



## H15 Topgrip (Reinforced)



이름	BXH(mm)	TRACTION RATING(DN)	ELONGATION (%)	RECOMMENDED PULLEY(mm)	MINIMUM PULLEY(mm)
H15GAC13TO	13 X 15	A	30	120	110
H15GAC13TO	17 X 20	B	50	135	120
H15GAC13TO	22 X 25	C	75	220	200

## DEL/FLEX Topgrip



DFVRCR13TO	13 x 15	A	14	5	110	100
DFVRCR17TO	17 x 20	B	25	5	125	110
DFVRCR22TO	22 x 25	C	42	5	200	180

## SOUPLEX Topgrip (Reinforced)



SXVWAC13TO	13 X 15	A	25	0.5	105	95
SXVWAC17TO	17 X 20	B	40	1	115	100
SXVWAC22TO	22 x 25	C	60	1.5	190	170

## SOUPLEX Topgrip



SXVMCR13TO	13 X 15	A	8	8	100	90
SXVMCR17TO	17 X 20	B	15	8	105	95
SXVMCR22TO	22 X 25	C	25	8	180	160

## DEL/FLEX Shape I - 7각



DFVRCR13F1	13 X 15	*A	22	5	120	100
DFVRCR17F1	17 X 20	B	35	5	150	120
DFVRCR22F1	22 X 25	C	56	5	210	180

\* 주문에 의한 제작

## DEL/FLEX Shape II - 5각



DFVRCR13F2	13 X 15	A	22	5	120	100
DFVRCR17F2	17 X 20	B	35	5	170	140
DFVRCR22F2	22 X 25	C	56	5	220	190

	경도	Recommended Tensioning	Steel	Stainless Steel	H.D.P.E
DEL/FLEX	90A	3-6%	0.5	0.6	0.25
SOUPLEX	85A	5-8%	0.6	0.7	0.35
H15 (심체형)	90A		0.45	0.55	0.25
SOUPLEX (심체형)	85A		0.6	0.7	0.35